



HC70

SPECIFICATIONS

HC series is especially used for engine starting, which requires superior cranking performance at lower temperatures, for high current discharge.

BATTERY DESIGN

- Absorbent glass mat (AGM) technology 12V battery VRLA
- Can be mounted in any orientation except inverted.
- US DOT and IATA certified non-spillable
- Can be fitted with TP brass automotive adaptor and protective steel case on request.
- BCI Group:93
- Shipped fully charged - just install and go!
- Suited for repeated discharges such as running your vehicle with winches or other electrical accessories.

PERFORMANCE FEATURES

- ✧ PHCA: 1650A at 80°F (27°C) for 5 seconds
- ✧ CCA: 900A at 0°F (-18°C)
- ✧ CA/MCA: 1080A at 32°F (0°C)
- ✧ HCA: 1255A at 80°F (27°C)
- ✧ Reserve capacity: 160 minutes
- ✧ Short circuit current: 3000A
- ✧ Terminal hardware torque: 89 lbf-in max
- ✧ Operation temperature range: -5°F (-15°C) to 122°F (50°C)

Nominal Dimensions

Length		Width		Height		Total Height		Weight	
mm	in	mm	in	mm	in	mm	in	kg	pound
351	13.82	167	6.57	179	7.05	179	7.05	24.80	54.63

HIGH RATE DISCHARGE AT 77°F (25°C)

5 sec.	10 sec.	15 sec.	20 sec.
1650A	1485A	1340A	1290A

EXTENDED DISCHARGE AT 77°F (25°C) TO 10.02V

5min	15min	1hr	3hr	5hr	10hr	20hr
285A	137A	44.5A	18A	12.1A	6.6A	3.6A

PHYSICAL CHARACTERISTICS

