

# **ODP-AGM34M** (ELT-AGM34M)

# **Technical Data Sheet**

#### **Battery Type**

AGM with Thin Plate Pure Lead (TPPL). Advanced dual-purpose battery for engine start and deep-cycle use

#### **Power & Performance**

Voltage	12V
Capacity (20-hour rate)	60Ah
Capacity (10-hour rate)	56Ah
Cold Cranking Amps (CCA, SAE J537)	710A
PHCA - 5-second pulse current	1300A
HCA	950A
MCA	810A
Reserve capacity	120 mins
Short circuit current (using IEC method)	1850A
Internal resistance at 20°C (using IEC method)	$4.9~\text{m}\Omega$

#### **Dimensions & Weight**

Length	277 mm
Width	173 mm
Height (to top of terminals)	198 mm
Height Container	183 mm
Weight	21.2 kg

#### **Temperature**

Operating Temperature Range	-40°C to +60°C
Optimum Storage Temperature	+20°C

#### Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

### **Charging & self-discharge**

Type of charging curve	100
Charge voltage @+20°C	14.4V to 14.8V
Self-discharge per month at +20°C	1.25%
Self-discharge per month at +40°C	5%

#### Fitting, handling & storage


Can be mounted or stored in any orientation except inverted. 2-years storage life at +20°C without charging, or until the Open Circuit Voltage (OCV) is <12.6V or <2.10Vpc, whichever occurs first. Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for dangerous Goods) and ICAO (International Civil Aviation Organisation).




# **Terminal Position**

# Dual Terminal

## **Terminal Type**





PDF Generated at https://eu.odysseybattery.com 17/11/2021 08:26:06 Information correct at time of exporting PDF. Please check website for updates.



EnerSys World Headquarters 2366 Bernville Road Reading, PA 19605,USA Tel: +1-610-208-1991 / +1-800-538-3627

EnerSys EMEA EH Europe GmbH Baarerstrasse 18 6300Zug, Switzerland

EnerSys Asia 152 Beach Road Gateway East Building #11-08 Singapore 189721 Tel: +65 6508 1780