

# ODYSSEY<sup>®</sup> BATTERY

## ODP-AGM75 86 (75/86-705)

### Technical Data Sheet

#### Battery Type

AGM with Thin Plate Pure Lead (TPPL). Advanced dual-purpose battery for engine start and deep-cycle use

#### Power & Performance

Voltage	12V
Capacity (20-hour rate)	49Ah
Capacity (10-hour rate)	45Ah
Cold Cranking Amps (CCA, SAE J537)	708A
PHCA - 5-second pulse current	1100A
HCA	875A
MCA	760A
Reserve capacity	89 mins
Short circuit current (using IEC method)	2200A
Internal resistance at 20°C (using IEC method)	2.8 mΩ

#### Dimensions & Weight

Length	241 mm
Width	173 mm
Height (to top of terminals)	201 mm
Height Container	188 mm
Weight	19.7 kg

#### Temperature

Operating Temperature Range	-40°C to +60°C
Optimum Storage Temperature	+20°C

#### Accreditations

The management systems governing the manufacture of this product are ISO 9001 and ISO 14001 certified.

#### Charging & self-discharge


Type of charging curve	IUU
Charge voltage @+20°C	14.4V to 14.8V
Self-discharge per month at +20°C	1.25%
Self-discharge per month at +40°C	5%

#### Fitting, handling & storage



Can be mounted or stored in any orientation except inverted. 2-years storage life at +20°C without charging, or until the Open Circuit Voltage (OCV) is <12.6V or <2.10Vpc, whichever occurs first. Classified as non-spillable and approved as non-hazardous cargo for ground, sea and air transportation in accordance with the requirements of IMDG (International Maritime code for dangerous Goods) and ICAO (International Civil Aviation Organisation).



#### Terminal Position



#### Terminal Type



**ODP-AGM75/86  
LEFT POSITIVE  
DUAL TERMINALS  
(SAE & SIDE)**

